

MeCAN™ - Mechanical Engine to J1939 CAN Interface



Features

- Integrates mechanical, non-ECU engines and sensors into J1939 instrument systems
- Inputs for speed sensors, resistive senders and fault switches
- Compact, sealed epoxy-filled case

MeCAN™ is a compact, encapsulated interface module that translates resistive sender, fault switch and speed signals into SAE J1939 CANbus data. MeCAN allows quick and simple integration of 'mechanical', non-ECU engines into modern CANbus systems. Applications include the retrofit of older engine fleets with modern digital instruments, controls and telemetry, and the development of standard control panels for both ECU and non-ECU engines.

MeCAN has three sensor inputs and one output. Two inputs are for oil pressure and coolant temperature sensing, either by fault switches or resistive senders. The third input measures engine speed, using a magnetic pickup or charge alternator signal. Input signals are translated into SAE J1939 CANbus messages with appropriate PGN address, data scaling and transmission rate. The 'shutdown' output operates and latches if the pressure, temperature or speed inputs deviate outside preset fault limits.

A fourth input is connected to a speed calibration potentiometer during setup mode only. DIP switches allow selection of normal/setup mode and two speed input ranges. An LED gives indication of operating mode and CANbus activity.

MeCAN is compact and light enough for inclusion in engine wiring harnesses, but can also be surface mounted. The case is fully sealed in epoxy resin for high impact and environmental resistance. Two standard versions allow use with either fault switches or Murphy ES series resistive senders. Custom solutions are also available for non-standard, volume OEM requirements.

Specifications

Power supply

Operating voltage: 7 to 35 VDC
Current consumption: 25mA (typ.)

Inputs

Maximum operating range: -2 to +35 VDC max.
Oil pressure, coolant temperature (model MEC301-1):
for Murphy ES(2)P and ES(2)T series resistive senders
Oil pressure, coolant temperature (model MEC301-2):
for fault switch, closing to negative DC on fault
Speed (magnetic pickup): opto-isolated, 3 – 30 Vrms,
adjustable 10 – 180 pulses per rev
Speed calibration: 0 – 5 kOhm potentiometer (setup only)

How to order

part number	model/description
79.70.0014	MEC301-1 MeCAN I/O module, for use with Murphy ES(2)P pressure and ES(2)T temperature senders
79.70.0020	MEC301-2 MeCAN I/O module, for use with pressure & temperature switches (closing to negative DC on fault)


Outputs (all ratings non-reactive)

Shutdown: negative DC (open collector transistor), 250mA max.
CANbus: SAE J1939 protocol, 120 Ohm terminating resistor fitted

Physical

Case material: high impact ABS, epoxy filled
Dimensions: see diagram below.
Weight: approx 60 g / 0.13 lb
Operating temperature: -20 to +85 °C / -4 to +185 °F
Environmental sealing:
IP65 case (with DIP switch protective film intact), exposed lead ends
Electromagnetic compatibility: 2004/108/EC

Connection & Dimensions



Warranty - A limited warranty on materials and workmanship is given with this FW Murphy product.
A copy of the warranty may be viewed or printed by going to <http://www.fwmurphy.com/warranty>